

Date: Tuesday, 7/1/2008 2:35:06 PM
User: Kim Johnston

Process Sheet

Customer : CU-DAR001 Dart Helicopters Services	Drawing Name : SADDLE FITTING, AFT (OUTBOARD/INBOARD)
Job Number : 40198	
Estimate Number : 10533	
P.O. Number :	Part Number : D2573
This Issue : 7/1/2008 S.O. No. :	Drawing Number : D2573 REV E
Prsht Rev. : NC	Project Number : N/A
First Issue : / / Type : MACHINED PARTS	Drawing Revision : E
Previous Run : 39808	Material :
Written By :	Due Date : 7/23/2008 Qty: 10 Um: Each
Checked & Approved By : <u>08.07.01</u>	
Comment : Est. I As Per RevE 06-01-27 JLM	

Additional Product

Job Number:



Seq. #:	Machine Or Operation:	Description :
---------	-----------------------	---------------

1.0	D6101007	Saddle Billet
-----	----------	---------------



Comment: Qty.: 1.0000 Each(s)/Unit Total : 6.0000 Each(s)
7075-T7351 8.25X7.75X2.5
Make from D6101-007 billet for D2573
Ensure that grain is along 7.75" length
Batch No: B24875

J.F. 08/08/20 (10)

2.0	HAAS1	HAAS CNC VERTICAL MACHINING #1
-----	-------	--------------------------------



Comment: HAAS CNC VERTICAL MACHINING #1
Program Batch No. 9098 Double check by: JS

1-Machine Step No 1 per Folio FA051 and inspect per attached Dimension Sheets
2-Machine Step No 2 per Folio FA051 and inspect per attached Dimension Sheets
3-Machine Step No 3 per Folio FA051 and inspect per attached Dimension Sheets
4-Deburr and remove all machining marks
5-Tumble to remove sharp edges.

J.F. / Pmk 08/08/22 (10)

3.0	MILLING CONV.	CONVENTIONAL MILLING MACHINE
-----	---------------	------------------------------



Comment: CONVENTIONAL MILLING MACHINE
Machine keyway as per dwg D2573 & D2574

J.F. / Pmk 08/08/22 (10)

4.0	QC2	INSPECT PARTS AS THEY COME OFF MACHINE
-----	-----	--



Comment: INSPECT PARTS AS THEY COME OFF MACHINE

J.F. / Pmk 08/08/22 (10)

Dart Aerospace Ltd

W/O:		WORK ORDER CHANGES					
DATE	STEP	PROCEDURE CHANGE	By	Date	Qty	Approval Chief Eng / Prod Mgr	Approval QC Inspector

Part No: _____ PAR #: _____ Fault Category: _____ NCR: Yes No DQA: _____ Date: _____

QA: N/C Closed: _____ Date: _____

NCR:		WORK ORDER NON-CONFORMANCE (NCR)						
DATE	STEP	Description of NC Section A	Corrective Action Section B			Verification Section C	Approval Chief Eng	Approval QC Inspector
			Initial Chief Eng	Action Description Chief Eng	Sign & Date			

NOTE: Date & initial all entries

Date: Tuesday, 7/1/2008 2:35:06 PM
User: Kim Johnston

Process Sheet

Customer: CU-DAR001 Dart Helicopters Services

Drawing Name: SADDLE FITTING, AFT (OUTBOARD/INBOARD)

Job Number: 40198

Part Number: D2573

Job Number:



Seq. #:

Machine Or Operation:

Description :

5.0

QC8

SECOND CHECK



Comment: SECOND CHECK

SS 08/08/23

6.0

HAND FINISHING1

HAND FINISHING RESOURCE #1



Comment: HAND FINISHING RESOURCE #1

Acid etch and Alodine as per QSI 005 4.1

HL

08-08-25

X10

7.0

POWDER COATING

POWDER COATING



M108523



10X

Comment: POWDER COATING

Powder Coat White Gloss (Ref: 4.3.5.1) as per QSI 005 4.3

START TIME:

11:40

OVEN TEMPERATURE:

320 OF

FINISH TIME:

12:10

M-L

08/08/25

8.0

QC3

INSPECT POWDER COAT/CHEMICAL CONVERSION



Comment: INSPECT POWDER COAT

08-08-25

X10

9.0

PACKAGING 1

PACKAGING RESOURCE #1



Comment: PACKAGING RESOURCE #1

Identify and Stock

Location: 433

8/8/25

10X

SP

10.0

QC21

FINAL INSPECTION/W/O RELEASE



Comment: FINAL INSPECTION/W/O RELEASE

08/08/26

Job Completion



u 08.08.26

W/O:		WORK ORDER CHANGES					
DATE	STEP	PROCEDURE CHANGE	By	Date	Qty	Approval Chief Eng / Prod Mgr	Approval QC Inspector

Part No: _____ PAR #: _____ Fault Category: _____ NCR: Yes No DQA: _____ Date: _____

QA: N/C Closed: _____ Date: _____

NCR:		WORK ORDER NON-CONFORMANCE (NCR)						
DATE	STEP	Description of NC Section A	Corrective Action Section B			Verification Section C	Approval Chief Eng	Approval QC Inspector
			Initial Chief Eng	Action Description Chief Eng	Sign & Date			

NOTE: Date & initial all entries

DART AEROSPACE LTD	Work Order:	40198
Description: Saddle, Aft Outboard	Part Number:	D2573
Inspection Dwg: D2573 Rev. E		Page 1 of 1

Inspect dimensions highlighted on inspection sheet drawing D2573 Rev. E and record below:

				Recorded Actual Dimensions					
Dim	Min	Max	Go/No Go Gauge	1	2	3	4	By	Date
A	0.438	0.443		0.439"	.440	.440	.441		
B	1.745	1.755		1.750"	1.750	1.750	1.749		
C	3.495	3.505		3.500"	3.500	3.500	3.500		
D	1.745	1.755		1.750"	1.750	1.750	1.749		
E	7.990	8.010		8.005"	8.000	8.000	8.000		
F	0.490	0.510		.510"	.501	.505	.500		
G	0.257	0.262		0.258"	0.258"	0.258"	.260		
H	0.375	0.380		0.377"	0.377"	0.377"	.378		
I	0.490	0.510		.504"	.510"	.510"	.510		
J	1.174	1.184		1.179"	1.179"	1.179"	1.178		
K	0.558	0.578		.568"	.576"	.577"	.578		
L	1.174	1.184		1.179"	1.179"	1.179"	1.178		
M	1.365	1.375		1.370"	1.370"	1.370"	1.370		
N	2.495	2.505		2.500"	2.502"	2.502"	2.500		
O	4.119	4.129		4.125"	4.125"	4.125"	4.125		
P	0.115	0.135		.126"	.126"	.126"	.127		
Q	0.115	0.135		.130"	.130"	.130"	.135		
R	0.240	0.260		.252"	.252"	.252"	.252		
S	0.115	0.135		.125"	.124"	.125"	.124		
T	0.178	0.198		R.188"	R.188"	R.188"	.188		
U	3.210	3.250		3.230"	3.230"	3.230"	3.228		
V	0.230	0.250		.239"	.240"	.239"	.240		
W	0.115	0.135		.126"	.120"	.120"	.125		
X	0.308	0.313		.312"	.311"	.311"	.311		
Y	0.760	0.765		.761"	.760"	.761"	.761		
Z	0.352	0.372		.368"	.369"	.369"	.369		
AA	0.470	0.530		R.500"	R.500"	R.500"	.500		
AB	0.615	0.635		.630"	.629"	.626"	.625		
AC	0.053	0.073		.063"	0.063"	0.063"	.063		
AD	0.240	0.260		.252"	.251"	.252"	.247		
AE	1.500	1.520		1.512"	1.513"	1.513"	1.514		
AF	0.115	0.135		.135"	.135"	.135"	.128		
AG	0.240	0.280		.273"	.273"	.273"	.265		
AH	0.240	0.260		.251"	.251"	.251"	.248		
AI	2.000	2.020		2.002"	2.002"	2.003"	2.000		
AJ	0.023	0.043		.033"	.033"	.033"	.033		
Accept/Reject									

Measured by:	J.F. / amf
Date:	08/08/20

Audited by:	SP
Date:	08/08/23

Rev	Date	Change	Revised by	Approved
A		New Issue	RF	
B	02.09.26	Re-format; Added Rev. D	KJ	
C	02.10.11	Re-format; Added DT8682, DT8683, DT8684	KJ	
D	05.05.05	Added dimension AI	KJ/RF	
E	05.12.05	Added dimension AJ	KJ/JLM	

DART AEROSPACE LTD	Work Order:	40198
Description: Saddle, Aft Outboard	Part Number:	D2573
Inspection Dwg: D2573 Rev. E		Page 1 of 1

Inspect dimensions highlighted on inspection sheet drawing D2573 Rev. E and record below:

				Recorded Actual Dimensions					
Dim	Min	Max	Go/No Go Gauge	1	2	3	4	By	Date
A	0.438	0.443		.440	.440	.440	.440		
B	1.745	1.755		1.749	1.750	1.750	1.750		
C	3.495	3.505		3.500	3.500	3.500	3.500		
D	1.745	1.755		1.749	1.750	1.750	1.750		
E	7.990	8.010		8.000	8.000	8.000	8.000		
F	0.490	0.510		.504	.502	.503	.502		
G	0.257	0.262		.260	.260	.260	.260		
H	0.375	0.380		.378	.378	.378	.378		
I	0.490	0.510		.501	.500	.501	.501		
J	1.174	1.184		1.179	1.179	1.180	1.180		
K	0.558	0.578		.570	.569	.569	.570		
L	1.174	1.184		1.179	1.179	1.180	1.179		
M	1.365	1.375		1.370	1.370	1.369	1.369		
N	2.495	2.505		2.500	2.500	2.500	2.500		
O	4.119	4.129		4.124	4.124	4.125	4.124		
P	0.115	0.135		.127	.127	.126	.126		
Q	0.115	0.135		.135	.135	.135	.135		
R	0.240	0.260		.252	.252	.251	.252		
S	0.115	0.135		.125	.121	.122	.123		
T	0.178	0.198		.188	.188	.188	.188		
U	3.210	3.250		3.229	3.229	3.229	3.229		
V	0.230	0.250		.241	.240	.240	.239		
W	0.115	0.135		.127	.129	.128	.128		
X	0.308	0.313		.311	.311	.311	.311		
Y	0.760	0.765		.766	.760	.766	.760		
Z	0.352	0.372		.367	.366	.366	.366		
AA	0.470	0.530		.500	.500	.500	.500		
AB	0.615	0.635		.630	.630	.630	.630		
AC	0.053	0.073		.063	.063	.063	.063		
AD	0.240	0.260		.246	.246	.247	.248		
AE	1.500	1.520		1.512	1.512	1.513	1.513		
AF	0.115	0.135		.122	.122	.123	.123		
AG	0.240	0.280		.261	.266	.265	.265		
AH	0.240	0.260		.249	.249	.249	.249		
AI	2.000	2.020		2.001	2.000	2.001	2.001		
AJ	0.023	0.043		.033	.033	.033	.033		
Accept/Reject									

Measured by:	me
Date:	08/08/22

Audited by:	SP
Date:	25/08/23

Rev	Date	Change	Revised by	Approved
A		New Issue	RF	
B	02.09.26	Re-format; Added Rev. D	KJ	
C	02.10.11	Re-format; Added DT8682, DT8683, DT8684	KJ	
D	05.05.05	Added dimension AI	KJ/RF	
E	05.12.05	Added dimension AJ	KJ/JLM	

DART AEROSPACE LTD	Work Order: 40198
Description: Saddle, Aft Outboard	Part Number: D2573
Inspection Dwg: D2573 Rev. E	Page 1 of 1

Inspect dimensions highlighted on inspection sheet drawing D2573 Rev. E and record below:




				Recorded Actual Dimensions					
Dim	Min	Max	Go/No Go Gauge	1	2	3	4	By	Date
A	0.438	0.443		.439	.446				
B	1.745	1.755		1.750	1.750				
C	3.495	3.505		3.506	3.500				
D	1.745	1.755		1.750	1.750				
E	7.990	8.010		8.606	8.006				
F	0.490	0.510		.501	.563				
G	0.257	0.262		.266	.260				
H	0.375	0.380		.378	.378				
I	0.490	0.510		.502	.500				
J	1.174	1.184		1.179	1.179				
K	0.558	0.578		.569	.567				
L	1.174	1.184		1.179	1.179				
M	1.365	1.375		1.376	1.370				
N	2.495	2.505		2.500	2.506				
O	4.119	4.129		4.124	4.124				
P	0.115	0.135		.126	.126				
Q	0.115	0.135		.135	.135				
R	0.240	0.260		.252	.257				
S	0.115	0.135		.121	.124				
T	0.178	0.198		.188	.188				
U	3.210	3.250		3.229	3.229				
V	0.230	0.250		.246	.239				
W	0.115	0.135		.127	.128				
X	0.308	0.313		.311	.311				
Y	0.760	0.765		.766	.766				
Z	0.352	0.372		.364	.365				
AA	0.470	0.530		.506	.500				
AB	0.615	0.635		.620	.628				
AC	0.053	0.073		.063	.063				
AD	0.240	0.260		.246	.245				
AE	1.500	1.520		1.513	1.512				
AF	0.115	0.135		.125	.124				
AG	0.240	0.280		.265	.265				
AH	0.240	0.260		.249	.247				
AI	2.000	2.020		2.000	2.000				
AJ	0.023	0.043		.033	.033				
Accept/Reject									

Measured by:	aml
Date:	08/08/22

Audited by:	LP
Date:	08/08/23

Rev	Date	Change	Revised by	Approved
A		New Issue	RF	
B	02.09.26	Re-format; Added Rev. D	KJ	
C	02.10.11	Re-format; Added DT8682, DT8683, DT8684	KJ	
D	05.05.05	Added dimension AI	KJ/RF	
E	05.12.05	Added dimension AJ	KJ/JLM	

05.12.06









SECTION A-A


DETAIL C
SCALE 4:3




NOTES

MATERIAL: 7075-T7351 (QQ-A-250/12)
(REF DART SPEC. D6102-001)
FINISH: ACID ETCH, ALODINE PER DART QSI 005 4.1
POWDER COAT GLOSS WHITE (REF 4.3.5.1) PER
DART QSI 005 4.3
BREAK ALL SHARP EDGES 0.010 TO 0.020
TOLERANCES ARE PER DART QSI 018 UNLESS OTHERWISE NOTED

- | | |
|---|---|
|  | ENGRAVE PART AND BATCH NUMBER IN THIS AREA TO MAX DEPTH OF 0.010 |
|  | ENGRAVE DART LOGO TO MAX DEPTH OF 0.015 WITH MIN RAD 0.125 |
|  | CHAMFER 0.063" x 45° AROUND THIS SURFACE (TYPICAL 2 PLACES) |
|  | CHAMFER 0.063" x 45° ALL AROUND |
|  | CHAMFER 0.033" x 45° (SEE DETAIL C)  |

VIEW B-B



E	05.07.13	ADD CHAMFER ON RIDGE NOTE 5
D	02.09.06	ADD RIDGES; TIGHTEN TOLERANCES
C	99.10.22	INCORP. DEO 9123/9079/9102 ADD DIMENSIONS PER TSR A1177
B	96.12.02	ADD GRAIN DIR., 0.438 WAS 0.425
A	96.09.16	NEW ISSUE
DESIGN		DRAWN BY
DS	PH	
CHECKED	APPROVED	DRAWING NO.
		D2573
DATE		TITLE
05.07.13		OUTER AFT SADDLE

COPYRIGHT © 2005 BY DART AEROSPACE LTD.

THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL
AND IS SUPPLIED ON THE EXPRESS CONDITION
THAT IT IS NOT TO BE USED FOR ANY PURPOSE
OR COPIED OR COMMUNICATED TO ANY OTHER
PERSON WITHOUT WRITTEN PERMISSION FROM
DART AEROSPACE LTD.

DART DART AEROSPACE LTD
HAMPSHIRE, ONTARIO, CANADA

DRAWING NO.	REV. E
D2573	SHEET 1 OF 1
TITLE	SCALE
OUTER AFT SADDLE	2:1

SECTION A
SHOP COPY
RETURN TO
ENGINEERING
UNCONTROLLED COPY
SUBJECT TO AMENDMENT
WITHOUT NOTICE
WORK ORDER
NO. 40138